

Wood+Apply Wood+Apply

HYBRID POLYMER TECHNOLOGY

HIGH PERFORMANCE ADHESIVE

Wood+Apply

HIGH PERFORMANCE ADHESIVE

SOLVENT FREE

RAPID ADHESION

MULTI-USE

10.1 oz (299 ml)

ENVIRONMENTALLY FRIENDLY

COMMON USES

- Steel
- Aluminum
- Coated Metal
- Glass
- Wood
- Concrete
- Masonry
- FRP
- Ceramics
- Styrofoam®
- Polycarbonate
- ABS
- PVC

Not suitable for marine applications or other applications when fully submerged under water for extended periods of time.

DANGER

Keep out of reach of children. Use only as directed.

PRECAUTIONARY STATEMENTS

Do not use until all instructions and safety precautions have been read and understood. Wear protective gloves, protective clothing, and eye protection. Wash contaminated work clothing before use. Contaminated work clothing should not be allowed out of the workplace. IF ON SKIN: Wash exposed body areas with soap and water. IF IN EYES: Rinse with water, remove contact lenses and continue rinsing. If exposed or concerned: Get medical advice/attention. Refer to Safety Data Sheet (SDS) for further information.

HAZARD STATEMENT

Harmful if swallowed. May cause an allergic reaction. May cause cancer. May damage fertility or the unborn child.



This product can expose you to chemicals, including DINP which is known in the state of California to cause cancer. For more information go to: www.p65Warnings.ca.gov

WA1164 is a one-component elastomeric adhesive designed to provide rapid fixturing strength between joined components. During cure, strength will increase resulting in a strong yet highly flexible bond between many substrates. WA1164 provides high performance for many assembly applications including adhesion to steel, aluminum, ceramics, Styrofoam®, coated metal, glass, wood, FRP, concrete, and many plastics (Polycarbonate, ABS, and PVC).

WA1164 is based on moisture cure technology meaning that it will react and cross-link in the presence of moisture.

INSTRUCTIONS

SURFACE PREPARATION

Surfaces Must be clean, fully dry, and free from dust, dirt, and grease. Do not apply in temperatures lower than 40F.

APPLICATION

Apply adhesive to the substrate as needed.

CLEAN UP

Clean tools and any uncured adhesive with mild solvent such as mineral spirits.

STORAGE AND DISPOSAL

Store securely between 60-80 F in unopened container. Recommended shelf life is 10 months from date of manufacture on bottom of tube. Keep tube tightly sealed. Dispose of contents/container in accordance with Local/Regional/National/International Regulations. Refer to Safety Data Sheet (SDS) for further information.

LIMITED WARRANTY

WoodApply warrants that our products are manufactured and conform to strict quality assurance specifications.

For warranty information visit: www.woodapply.com



Woodstock Architectural Products

5070 W Patrick Ln,
Las Vegas, NV 89118
702.363.3737

www.woodstockap.com

MADE IN THE USA